Casa Single DL, version 110 LO 1981 88 6

There are more versions of **Casa Single DL** available at <u>lival.com</u> Small, multi-axis tilting recessed downlight. Designed for all interior lighting needs with its various optics options, clean design and easy installation.



Article Number 110 L0 19 81 88 6 Family Name Casa Single DL Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Folliliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Folliliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K Folliliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K Folliliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K BRI 4000K, 5000K BRI 400K,	Lightsource	LED
Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Qendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below	Article Number	110 L0 19 81 88 6
Adapter Type Array Mounting Type Light Source Product Name Control Gear Control Gear Light Distribution Control Gear Luminous Flux Luminous Flux Efficacy (Im/W) COB Flux Color Temperature Color Rendering Index Ra 90 Color Of Housing White IP Rating Light Source Options Color Consistency Material Array Citizen CLU038-1206/930BBL Citizen CLU038-1206/930BBL Citizen CLU038-1206/930BBL Array Array Array Citizen CLU038-1206/930BBL Array Arr	Family Name	Casa Single DL
Mounting Type Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K CRI 90+ 2700K Below BBL, 3000K GRI 90+ 2700K Below BBL, 300K B	Luminaire Type	Downlight
Light Source Product Name Control Gear Control Gear Control Gear Control Gear Convoff, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux Efficacy (Im/W) COB Flux Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BBL, 300K B	Adapter Type	Array
Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Mounting Type	Array
Light Distribution Array Wattage 28 W Luminous Flux 2443 lm Efficacy (lm/W) 87 lm/W COB Flux 3010 lm Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/930BBL
Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Meat 2000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K	Control Gear	on/off, DALI, BLL
Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Array
Efficacy (Im/W) COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Wattage	28 W
COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	2443 lm
Color Temperature3000 KColor Rendering IndexRa 90Color Of HousingWhiteIP Rating23Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCMMaterialPowder painted die-cast aluminium	Efficacy (Im/W)	87 lm/W
Color Rendering Index Color Of Housing White IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	COB Flux	3010 lm
Color Of Housing IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000 K
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 90
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	White
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	IP Rating	23
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,
<u>'</u>	Color Consistency	MacAdams 2 SDCM
LIGR	Material	Powder painted die-cast aluminium
25.5	UGR	23.3





