Casa Single DL, version 110 LO 1981 88 9

There are more versions of **Casa Single DL** available at <u>lival.com</u> Small, multi-axis tilting recessed downlight. Designed for all interior lighting needs with its various optics options, clean design and easy installation.



Family Name Casa Single DL Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000 K Below BBL, 3000 K Below BBL, 3000 K Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium UGR 233	Lightsource	LED
Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BBL, 4000K, 5000K CRI 90+2700K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Article Number	110 L0 19 81 88 9
Adapter Type Array Mounting Type Light Source Product Name Control Gear Control Gear Light Distribution Wattage Luminous Flux Luminous Flux Efficacy (Im/W) COB Flux Color Temperature Color Rendering Index Ra 90 Color Of Housing Light Source Options Light Source Options Array Color Consistency Material Array Array Array Citizen CLU038-1206/930BBL Citizen CLU038-1206/930BBL Array Array Array Array Array Array Array Citizen CLU038-1206/930BBL Array	Family Name	Casa Single DL
Mounting Type Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 300K Below BBL, 300K	Luminaire Type	Downlight
Light Source Product Name Control Gear Control Gear Control Gear Light Distribution Array Wattage 28 W Luminous Flux Efficacy (Im/W) COB Flux Color Temperature Color Rendering Index Ra 90 Color Of Housing IP Rating CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BB	Adapter Type	Array
Control Gear on/off, DALI, BLL Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Mounting Type	Array
Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K Below BBL, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/930BBL
Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Below BBL, 3000K Below BBL, 300K B	Control Gear	on/off, DALI, BLL
Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K Meat 2000K, 8akery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Array
Efficacy (Im/W) COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Wattage	28 W
COB Flux 3010 Im Color Temperature 3000 K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	2443 lm
Color Temperature3000 KColor Rendering IndexRa 90Color Of HousingBlackIP Rating23Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCMMaterialPowder painted die-cast aluminium	Efficacy (Im/W)	87 lm/W
Color Rendering IndexRa 90Color Of HousingBlackIP Rating23Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCMMaterialPowder painted die-cast aluminium	COB Flux	3010 lm
Color Of Housing IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000 K
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 90
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	Black
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	IP Rating	23
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,
<u> </u>	Color Consistency	MacAdams 2 SDCM
UGR 23.3	Material	Powder painted die-cast aluminium
	UGR	23.3





