


Colt Lean, version 141 R0 14 44 13 6

There are more versions of **Colt Lean** available at lival.com
High performance and cost efficiency. Perfect for recessed tracks
due to flush installed polycarbonate housing.



Lightsource	LED
Article Number	141 R0 14 44 13 6
Family Name	Colt Lean
Luminaire Type	Tracklight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	on/off, DALI, BLL
Light Distribution	Array
Wattage	42 W
Luminous Flux	3982 lm
Efficacy (lm/W)	95 lm/W
COB Flux	4950 lm
Color Temperature	3000K
Color Rendering Index	Ra 80
Color Of Housing	White
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	23.4



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511