Colt Lean, version 141 R0 14 44 13 9

There are more versions of **Colt Lean** available at <u>lival.com</u> High performance and cost efficiency. Perfect for recessed tracks due to flush installed polycarbonate housing.


LightsourceLEDArticle Number141 R0 14 44 13 9Family NameColt LeanLuminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 ImEfficacy (Im/W)95 Im/WCOlor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Surce OptionsCRI 80+ 2700K, 3000K, 4000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 8400K, 5000K Meat 2000K, 840KMaterialPowder painted die-cast aluminium		
Family NameColt LeanLuminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 ImEfficacy (Im/W)95 Im/WCOB Flux4950 ImColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, 4000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 800K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 800K, 4000K, 5000K Meat 2000K, 800K, 4000K, 5000K Meat 2000K, 800K	Lightsource	LED
Luminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowBL, 4000K BFL, 3500K BelowBBL, 4000K BFL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Article Number	141 RO 14 44 13 9
Adapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 ImEfficacy (Im/W)95 Im/WCOB Flux4950 ImColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Family Name	Colt Lean
Mounting TypeArrayLight Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 lmEfficacy (Im/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 4000K	Luminaire Type	Tracklight
Light Source Product NameCitizen CLU038-1206/830Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K BelowBBL, 4000K Brilliant vivid 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K	Adapter Type	Array
Control Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Mounting Type	Array
Light DistributionArrayWattage42 WLuminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Light Source Product Name	Citizen CLU038-1206/830
Wattage42 WLuminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cifetime50 000h (L80 B10)Color ConsistencyMacAdams 2 SDCMColor ConsistencyMacAdams 2 SDCM	Control Gear	on/off, DALI, BLL
Luminous Flux3982 lmEfficacy (lm/W)95 lm/WCOB Flux4950 lmColor Temperature3000KColor Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Light Distribution	Array
Efficacy (Im/W)95 Im/WCOB Flux4950 ImColor Temperature3000KColor Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Wattage	42 W
COB Flux4950 lmColor Temperature3000KColor Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowLight Source OptionsBBL, 4000K Brilliant vivid 3000K, 4000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Luminous Flux	3982 lm
Color Temperature3000KColor Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Efficacy (Im/W)	95 lm/W
Color Rendering IndexRa 80Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K CRI 90+ 2400KColor ConsistencyMacAdams 2 SDCM	COB Flux	4950 lm
Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Temperature	3000K
IP Rating20Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Rendering Index	Ra 80
Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Of Housing	Black
Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	IP Rating	20
Light Source Options5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Lifetime	50 000h (L80 B10)
,	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,
Material Powder painted die-cast aluminium	Color Consistency	MacAdams 2 SDCM
	Material	Powder painted die-cast aluminium

UGR

LIVAL







For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511

23.4