Colt Lean, version 141 RO 19 44 12 9

There are more versions of **Colt Lean** available at <u>lival.com</u> High performance and cost efficiency. Perfect for recessed tracks due to flush installed polycarbonate housing.

	W	

LED Article Number 141 R0 19 44 12 9 Family Name Colt Lean Luminaire Type Tracklight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 42 W Luminous Flux 3311 Im Efficacy (Im/W) 79 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K BBL,				
Family NameColt LeanLuminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU038-1206/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage42 WLuminous Flux3311 lmEfficacy (lm/W)79 lm/WCOB Flux4050 lmColor Temperature3000KColor Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBI, 3000K Belo		LED		
Luminaire Type Adapter Type Array Mounting Type Light Source Product Name Citizen CLU038-1206/930BBL Control Gear Control Gear On/off, DALI, BLL Light Distribution Array Wattage 42 W Luminous Flux 3311 Im Efficacy (Im/W) 79 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Article Number	141 RO 19 44 12 9		
Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear On/off, DALI, BLL Light Distribution Array Wattage 42 W Luminous Flux 3311 lm Efficacy (lm/W) COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 300K	Family Name	Colt Lear		
Mounting Type Light Source Product Name Control Gear Cont	Luminaire Type	Tracklight		
Light Source Product Name Control Gear On/off, DALI, BLL Array Wattage 42 W Luminous Flux 3311 Im Efficacy (Im/W) COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BBL, 300K BBL	Adapter Type	Array		
Control Gear on/off, DALI, BLL Light Distribution Array Wattage 42 W Luminous Flux 3311 Im Efficacy (Im/W) 79 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 300K BBL, 3000K B	Mounting Type	Array		
Light Distribution Array Wattage 42 W Luminous Flux 3311 lm Efficacy (lm/W) 79 lm/W COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/930BBL		
Wattage 42 W Luminous Flux 3311 Im Efficacy (Im/W) 79 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BBL, 300K BBL, 3000K BBL	Control Gear	on/off, DALI, BLL		
Luminous Flux Efficacy (Im/W) COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, 8000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Array		
Efficacy (Im/W) COB Flux Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Meat 2000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Wattage	42 W		
COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	3311 lm		
Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Efficacy (Im/W)	79 lm/W		
Color Rendering Index Ra 90 Color Of Housing Black IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	COB Flux	4050 lm		
Color Of Housing IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000K		
IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 90		
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	Black		
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	IP Rating	20		
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)		
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,		
· ·	Color Consistency	MacAdams 2 SDCM		
UGR 22.7	Material	Powder painted die-cast aluminium		
	UGR	22.7		





