


Colt Lean, version 141 T0 22 44 12 6

There are more versions of **Colt Lean** available at lival.com
High performance and cost efficiency. Perfect for recessed tracks
due to flush installed polycarbonate housing.



| | |
|---------------------------|---|
| Lightsource | LED |
| Article Number | 141 T0 22 44 12 6 |
| Family Name | Colt Lean |
| Luminaire Type | Tracklight |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | Citizen CLU048-1212/830 |
| Control Gear | on/off, DALI, BLL |
| Light Distribution | Array |
| Wattage | 55 W |
| Luminous Flux | 5858 lm |
| Efficacy (lm/W) | 107 lm/W |
| COB Flux | 7050 lm |
| Color Temperature | 3000K |
| Color Rendering Index | Ra 80 |
| Color Of Housing | White |
| IP Rating | 20 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 21.4 |



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511