


# Colt Lean, version 141 T0 22 44 13 9

There are more versions of **Colt Lean** available at [lival.com](http://lival.com)  
High performance and cost efficiency. Perfect for recessed tracks  
due to flush installed polycarbonate housing.



Lightsource	LED
Article Number	141 T0 22 44 13 9
Family Name	Colt Lean
Luminaire Type	Tracklight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU048-1212/830
Control Gear	on/off, DALI, BLL
Light Distribution	Array
Wattage	55 W
Luminous Flux	5889 lm
Efficacy (lm/W)	107 lm/W
COB Flux	7050 lm
Color Temperature	3000K
Color Rendering Index	Ra 80
Color Of Housing	Black
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	24.7



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511