Colt Lean, version 141 T0 27 44 11 9

There are more versions of **Colt Lean** available at <u>lival.com</u> High performance and cost efficiency. Perfect for recessed tracks due to flush installed polycarbonate housing.


LightsourceLEDArticle Number141 T0 27 44 11 9Family NameColt LeanLuminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 ImEfficacy (Im/W)91 Im/WCOlor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Soook CRI 90+ 2700K Below BBL, 3000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K BelowLight Source OptionsColor ConsistencyMaterialPowder painted die-cast aluminium		
Family NameColt LeanLuminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 ImEfficacy (Im/W)91 Im/WCOB Flux5750 ImColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 300K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, 4000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 800K, 4000K, 5000K Meat 2000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 5000K	Lightsource	LED
Luminaire TypeTracklightAdapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 lmEfficacy (Im/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowBL, 4000K BFL, 3500K BelowBBL, 4000K BFL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Article Number	141 TO 27 44 11 9
Adapter TypeArrayMounting TypeArrayLight Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 ImEfficacy (Im/W)91 Im/WCOB Flux5750 ImColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Family Name	Colt Lean
Mounting TypeArrayLight Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 4000K	Luminaire Type	Tracklight
Light Source Product NameCitizen CLU048-1212/930BBLControl Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K BelowLight Source OptionsCRI 80+ 2700K, 3000K, 4000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K	Adapter Type	Array
Control Gearon/off, DALI, BLLLight DistributionArrayWattage55 WLuminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K BelowColor ConsistencyMacAdams 2 SDCM	Mounting Type	Array
Light DistributionArrayWattage55 WLuminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Light Source Product Name	Citizen CLU048-1212/930BBL
Wattage55 WLuminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cifetime50 000h (L80 B10)Color ConsistencyMacAdams 2 SDCMColor ConsistencyMacAdams 2 SDCM	Control Gear	on/off, DALI, BLL
Luminous Flux4978 lmEfficacy (lm/W)91 lm/WCOB Flux5750 lmColor Temperature3000KColor Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cell 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Light Distribution	Array
Efficacy (Im/W)91 Im/WCOB Flux5750 ImColor Temperature3000KColor Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2400KColor ConsistencyMacAdams 2 SDCM	Wattage	55 W
COB Flux5750 ImColor Temperature3000KColor Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Cifetime50 000h (L80 B10)Cight Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Luminous Flux	4978 lm
Color Temperature3000KColor Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Efficacy (Im/W)	91 lm/W
Color Rendering IndexRa 90Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	COB Flux	5750 lm
Color Of HousingBlackIP Rating20Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Temperature	3000K
IP Rating20Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Rendering Index	Ra 90
Lifetime50 000h (L80 B10)Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Color Of Housing	Black
Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	IP Rating	20
Light Source Options5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCM	Lifetime	50 000h (L80 B10)
,	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,
Material Powder painted die-cast aluminium	Color Consistency	MacAdams 2 SDCM
	Material	Powder painted die-cast aluminium

UGR

LIVAL







For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511

20.8