

# Colt Lean, version 141 T0 27 44 13 9

There are more versions of **Colt Lean** available at [lival.com](http://lival.com)  
High performance and cost efficiency. Perfect for recessed tracks  
due to flush installed polycarbonate housing.



|                           |   |
|---------------------------|---|
| Lightsource               | LED   |
| Article Number            | 141 T0 27 44 13 9   |
| Family Name               | Colt Lean   |
| Luminaire Type            | Tracklight  |
| Adapter Type              | Array   |
| Mounting Type             | Array   |
| Light Source Product Name | Citizen CLU048-1212/930BBL  |
| Control Gear              | on/off, DALI, BLL   |
| Light Distribution        | Array   |
| Wattage                   | 55 W  |
| Luminous Flux             | 5027 lm   |
| Efficacy (lm/W)           | 91 lm/W   |
| COB Flux                  | 5750 lm   |
| Color Temperature         | 3000K   |
| Color Rendering Index     | Ra 90   |
| Color Of Housing          | Black   |
| IP Rating                 | 20  |
| Lifetime                  | 50 000h (L80 B10)   |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K,<br>5000K CRI 90+ 2700K Below BBL,<br>3000K Below BBL, 3500K Below<br>BBL, 4000K Brilliant vivid 3000K,<br>4000K, 5000K Meat 2000K,<br>Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM   |
| Material                  | Powder painted die-cast aluminium   |
| UGR                       | 24.2  |

