

# Colt Mini Casa, version 167 L0 19 44 86 9

There are more versions of **Colt Mini Casa** available at [lival.com](http://lival.com)  
High performance in a very compact form factor. Perfect for recessed  
tracks due to flush installed polycarbonate housing.



|                           |                                                                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lightsource               | LED                                                                                                                                                                             |
| Article Number            | 167 L0 19 44 86 9                                                                                                                                                               |
| Family Name               | Colt Mini Casa                                                                                                                                                                  |
| Luminaire Type            | Tracklight                                                                                                                                                                      |
| Adapter Type              | Array                                                                                                                                                                           |
| Mounting Type             | Array                                                                                                                                                                           |
| Light Source Product Name | Citizen CLU038-1206/930BBL                                                                                                                                                      |
| Control Gear              | on/off, DALI                                                                                                                                                                    |
| Light Distribution        | Array                                                                                                                                                                           |
| Wattage                   | 28 W                                                                                                                                                                            |
| Luminous Flux             | 2443 lm                                                                                                                                                                         |
| Efficacy (lm/W)           | 87 lm/W                                                                                                                                                                         |
| COB Flux                  | 3010 lm                                                                                                                                                                         |
| Color Temperature         | 4000KK                                                                                                                                                                          |
| Color Rendering Index     | Ra 90                                                                                                                                                                           |
| Color Of Housing          | Black                                                                                                                                                                           |
| IP Rating                 | 20                                                                                                                                                                              |
| Lifetime                  | 50 000h (L80 B10)                                                                                                                                                               |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K,<br>5000K CRI 90+ 2700K Below BBL,<br>3000K Below BBL, 3500K Below<br>BBL, 4000K Brilliant vivid 3000K,<br>4000K, 5000K Meat 2000K,<br>Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM                                                                                                                                                                 |
| Material                  | Powder painted die-cast aluminium                                                                                                                                               |
| UGR                       | 18.3                                                                                                                                                                            |



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your  
email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511