


# First Circle, version 10P R0 14 81 14 5

There are more versions of **First Circle** available at [lival.com](http://lival.com)  
Multi-axis tilting downlight for all indoor applications. First Circle can be used for both general or accent lighting.



|                           |   |
|---------------------------|---|
| Lightsource               | LED   |
| Article Number            | 10P R0 14 81 14 5   |
| Family Name               | First Circle  |
| Luminaire Type            | Downlight   |
| Adapter Type              | Array   |
| Mounting Type             | Array   |
| Light Source Product Name | Citizen CLU038-1206/830   |
| Control Gear              | on/off, BLL   |
| Light Distribution        | Array   |
| Wattage                   | 42 W  |
| Luminous Flux             | 4136 lm   |
| Efficacy (lm/W)           | 98 lm/W   |
| COB Flux                  | 4950 lm   |
| Color Temperature         | 3000 K  |
| Color Rendering Index     | Ra 80   |
| Color Of Housing          | Silver  |
| IP Rating                 | 20  |
| Lifetime                  | 50 000h (L80 B10)   |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K,<br>5000K CRI 90+ 2700K Below BBL,<br>3000K Below BBL, 3500K Below<br>BBL, 4000K Brilliant vivid 3000K,<br>4000K, 5000K Meat 2000K,<br>Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM   |
| Material                  | Powder painted die-cast aluminium   |
| UGR                       | 17.7  |



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511