


First Circle, version 10P T0 27 81 11 5

There are more versions of **First Circle** available at lival.com
Multi-axis tilting downlight for all indoor applications. First Circle can be used for both general or accent lighting.



Lightsource	LED
Article Number	10P T0 27 81 11 5
Family Name	First Circle
Luminaire Type	Downlight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU048-1212/930BBL
Control Gear	on/off, BLL
Light Distribution	Array
Wattage	55 W
Luminous Flux	4978 lm
Efficacy (lm/W)	91 lm/W
COB Flux	5750 lm
Color Temperature	3000 K
Color Rendering Index	Ra 90
Color Of Housing	Silver
IP Rating	23
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	18.9



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511