


First Circle, version 10P T0 27 81 11 9

There are more versions of **First Circle** available at lival.com
Multi-axis tilting downlight for all indoor applications. First Circle can be used for both general or accent lighting.



| | |
|---------------------------|---|
| Lightsource | LED |
| Article Number | 10P T0 27 81 11 9 |
| Family Name | First Circle |
| Luminaire Type | Downlight |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | Citizen CLU048-1212/930BBL |
| Control Gear | on/off, BLL |
| Light Distribution | Array |
| Wattage | 55 W |
| Luminous Flux | 4978 lm |
| Efficacy (lm/W) | 91 lm/W |
| COB Flux | 5750 lm |
| Color Temperature | 3000 K |
| Color Rendering Index | Ra 90 |
| Color Of Housing | Black |
| IP Rating | 23 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 18.9 |



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511