


# First Single, version 10A R0 14 81 12 5

There are more versions of **First Single** available at [lival.com](http://lival.com)  
Multi-axis tilting downlight for all indoor applications. First Single can be used for both general or accent lighting.



Lightsource	LED
Article Number	10A R0 14 81 12 5
Family Name	First Single
Luminaire Type	Downlight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	on/off, BLL
Light Distribution	Array
Wattage	42 W
Luminous Flux	3898 lm
Efficacy (lm/W)	93 lm/W
COB Flux	4950 lm
Color Temperature	3000 K
Color Rendering Index	Ra 80
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	21.5



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511