

First Single, version 10A T0 27 81 13 6

There are more versions of **First Single** available at lival.com
Multi-axis tilting downlight for all indoor applications. First Single can be used for both general or accent lighting.



| | |
|---------------------------|--|
| Lightsource | LED |
| Article Number | 10A T0 27 81 13 6 |
| Family Name | First Single |
| Luminaire Type | Downlight |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | Citizen CLU048-1212/930BBL |
| Control Gear | on/off, BLL |
| Light Distribution | Array |
| Wattage | 55 W |
| Luminous Flux | 5027 lm |
| Efficacy (lm/W) | 91 lm/W |
| COB Flux | 5750 lm |
| Color Temperature | 3000 K |
| Color Rendering Index | Ra 90 |
| Color Of Housing | White |
| IP Rating | 20 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 22.2 |

