GA-016 Bing, version 15A LO 19 40 86 6

There are more versions of **GA-016 Bing** available at <u>lival.com</u> Taking clean seamless design to a new extreme, Bing has no visible screws or cables and provides excellent light.

	W	

Article Number 15A L0 19 40 86 6 Family Name GA-016 Bing Luminaire Type Tracklight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BBL, 4000K Brilliant vivid 3000K			
Family Name GA-016 Bing Luminaire Type Tracklight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 300K	Lightsource	LED	
Luminaire Type Array Adapter Type Array Mounting Type Light Source Product Name Citizen CLU038-1206/930BBL Control Gear On/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux Efficacy (Im/W) R7 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below	Article Number	15A LO 19 40 86 6	
Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear On/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 300K Below BBL, 300K Below BBL, 300K Below BBL,	Family Name	GA-016 Bing	
Mounting Type Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K CRI 90+ 2700K Below BBL, 3000K BBL, 300K BBL	Luminaire Type	Tracklight	
Light Source Product Name Control Gear Control Gear Control Gear Light Distribution Marray Wattage Luminous Flux Efficacy (Im/W) COB Flux Color Temperature Color Of Housing IP Rating Light Source Options CRI 80+ 2700K, 3000K, 4000K, 5000K GRI 90+ 2700K Below BBL, 3000K BBL, 3500K Below BBL, 3000K BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K, 4000K, 6000K, 6	Adapter Type	Array	
Control Gear on/off, DALI, BLL, Casambi, PIR Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K BBL, 3000K BBL, 300K B	Mounting Type	Array	
Light Distribution Array Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/930BBL	
Wattage 28 W Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BBL, 300K	Control Gear	on/off, DALI, BLL, Casambi, PIR	
Luminous Flux 2443 Im Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Array	
Efficacy (Im/W) 87 Im/W COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BBL,	Wattage	28 W	
COB Flux 3010 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	2443 lm	
Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Efficacy (Im/W)	87 lm/W	
Color Rendering Index Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	COB Flux	3010 lm	
Color Of Housing IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000K	
IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 90	
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	White	
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Powder painted die-cast aluminium	IP Rating	20	
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)	
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,	
<u>`</u>	Color Consistency	MacAdams 2 SDCM	
UGR 21	Material	Powder painted die-cast aluminium	
	UGR	21	





