



GA-016 Bing, version 15A L0 14 40 85 6

There are more versions of **GA-016 Bing** available at lival.com
Taking clean seamless design to a new extreme, Bing has no visible screws or cables and provides excellent light.



Lightsource	LED
Article Number	15A L0 14 40 85 6
Family Name	GA-016 Bing
Luminaire Type	Tracklight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	on/off, DALI, BLL, Casambi, PIR
Light Distribution	Array
Wattage	29 W
Luminous Flux	2938 lm
Efficacy (lm/W)	101 lm/W
COB Flux	3700 lm
Color Temperature	3000K
Color Rendering Index	Ra 80
Color Of Housing	White
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	21.8



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511