GA-016 Cafeteria, version 153 NO 32 40 11 9

There are more versions of **GA-016 Cafeteria** available at <u>lival.com</u> Efficient Cafeteria head with an ultra slim track adapter. Great cooling and excellent light - great performance for value.



Article Number 153 NO 32 40 1 Family Name GA-016 Cafete Luminaire Type Tracklig Adapter Type Arr Mounting Type Arr Light Source Product Name Citizen CLU038-1208C4 Bake Control Gear on/off, DALI, BLL, Casambi, F Light Distribution Arr Wattage 33 Luminous Flux 2357 Efficacy (lm/W) 71 lm, COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	ED
Family Name GA-016 Cafete Luminaire Type Adapter Type Arm Mounting Type Light Source Product Name Control Gear Control Gear Light Distribution Wattage Luminous Flux Efficacy (Im/W) COB Flux Color Temperature CAPOLIA GARDALI	
Luminaire Type Adapter Type Ann Mounting Type Arn Light Source Product Name Control Gear Light Distribution Wattage Juminous Flux Efficacy (lm/W) COB Flux Color Temperature Color Rendering Index Tracklight Tra	19
Adapter Type Ari Mounting Type Ari Light Source Product Name Citizen CLU038-1208C4 Bake Control Gear on/off, DALI, BLL, Casambi, F Light Distribution Ari Wattage 33 Luminous Flux 2357 Efficacy (lm/W) 71 lm, COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	ria
Mounting Type Light Source Product Name Control Gear Control Gear Confol Gear	ght
Light Source Product Name Control Gear Control Gear Light Distribution Wattage Luminous Flux Efficacy (lm/W) COB Flux Color Temperature Color Rendering Index Citizen CLU038-1208C4 Bake	ay
Control Gear on/off, DALI, BLL, Casambi, F Light Distribution Arr Wattage 33 Luminous Flux 2357 Efficacy (Im/W) 71 Im. COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	ay
Light DistributionArrWattage33Luminous Flux2357Efficacy (lm/W)71 lm.COB Flux2730Color Temperature2400Color Rendering IndexRa	ery
Wattage 33 Luminous Flux 2357 Efficacy (Im/W) 71 Im. COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	PIR
Luminous Flux 2357 Efficacy (lm/W) 71 lm. COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	ay
Efficacy (Im/W) 71 Im. COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	W
COB Flux 2730 Color Temperature 2400 Color Rendering Index Ra	lm
Color Temperature 2400 Color Rendering Index Ra	W
Color Rendering Index Ra	lm
	ΣK
Color Of Housing Bl	98
Color Of Flodsing	ack
IP Rating	20
Lifetime 50 000h (L80 B	LO)
CRI 80+ 2700K, 3000K, 4000 5000K CRI 90+ 2700K Below B 3000K Below BBL, 3500K Bel BBL, 4000K Brilliant vivid 3000 4000K, 5000K Meat 2000 Bakery 240	BL, ow DK, DK,
Color Consistency MacAdams 4 SDC	M
Material Powder painted die-cast alumini	um
UGR 2	0.1





