



GA-016 Cafeteria, version 153 N0 36 40 12 9

There are more versions of **GA-016 Cafeteria** available at lival.com
Efficient Cafeteria head with an ultra slim track adapter. Great cooling and excellent light - great performance for value.



Lightsource	LED
Article Number	153 N0 36 40 12 9
Family Name	GA-016 Cafeteria
Luminaire Type	Tracklight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206 BV3000
Control Gear	on/off, DALI, BLL, Casambi, PIR
Light Distribution	Array
Wattage	34 W
Luminous Flux	2122 lm
Efficacy (lm/W)	62 lm/W
COB Flux	2450 lm
Color Temperature	3000 K
Color Rendering Index	Ra 90
Color Of Housing	Black
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 3 SDCM
Material	Powder painted die-cast aluminium
UGR	21



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511