# GA-016 Dingo, version 15X N0 19 40 11 6

There are more versions of **GA-016 Dingo** available at lival.com
All-new, seamless cylinder design, GA-016 Dingo with deep-cut aluminium reflector is the optimal solution for accent lighting.

| | |
|---|---|
| Lightsource | LED |
| Article Number | 15X N0 19 40 11 6 |
| Family Name | GA-016 Dingo |
| Luminaire Type | Tracklight |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | Citizen CLU038-1206/930BBL |
| Control Gear | on/off, DALI, BLL, Casambi, PIR |
| Light Distribution | Array |
| Wattage | 35 W |
| Luminous Flux | 2510 lm |
| Efficacy (lm/W) | 72 lm/W |
| COB Flux | 3360 lm |
| Color Temperature | 3000K |
| Color Rendering Index | Ra 90 |
| Color Of Housing | White |
| IP Rating | 20 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 3.8 |






