



# GA-016 Dingo, version 15X N0 14 40 12 5

There are more versions of **GA-016 Dingo** available at [lival.com](http://lival.com)  
All-new, seamless cylinder design, GA-016 Dingo with deep-cut aluminium reflector is the optimal solution for accent lighting.



|                           |                                                                                                                                                                  |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lightsource               | LED                                                                                                                                                              |
| Article Number            | 15X N0 14 40 12 5                                                                                                                                                |
| Family Name               | GA-016 Dingo                                                                                                                                                     |
| Luminaire Type            | Tracklight                                                                                                                                                       |
| Adapter Type              | Array                                                                                                                                                            |
| Mounting Type             | Array                                                                                                                                                            |
| Light Source Product Name | Citizen CLU038-1206/830                                                                                                                                          |
| Control Gear              | on/off, DALI, BLL, Casambi, PIR                                                                                                                                  |
| Light Distribution        | Array                                                                                                                                                            |
| Wattage                   | 35 W                                                                                                                                                             |
| Luminous Flux             | 2918 lm                                                                                                                                                          |
| Efficacy (lm/W)           | 83 lm/W                                                                                                                                                          |
| COB Flux                  | 4150 lm                                                                                                                                                          |
| Color Temperature         | 3000K                                                                                                                                                            |
| Color Rendering Index     | Ra 80                                                                                                                                                            |
| Color Of Housing          | Silver                                                                                                                                                           |
| IP Rating                 | 20                                                                                                                                                               |
| Lifetime                  | 50 000h (L80 B10)                                                                                                                                                |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM                                                                                                                                                  |
| Material                  | Powder painted die-cast aluminium                                                                                                                                |
| UGR                       | 5                                                                                                                                                                |



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511