Hony, version 10S S0 14 81 05 6

There are more versions of **Hony** available at <u>lival.com</u> Efficient luminaire with low profile - fits in suspended ceilings with very limited installation space.

	W	/	
	v	-	

Article Number 10S S0 14 81 05 6 Family Name Hony Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Brills vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 800K, 5000K Meat 2000K, 800K Bakery 2400K Material Powder painted die-cast aluminium UGR	Lightcourse	LED		
Family Name Hony Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K, 5000K Meat 2000K, 8akery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Lightsource			
Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) Light Source Options Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium				
Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 30	Family Name	Hony		
Mounting Type Light Source Product Name Control Gear Cont	Luminaire Type	Downlight		
Light Source Product Name Control Gear Color Distribution Color Temperature Color Gendering Index Color Of Housing IP Rating CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Bakery 2400K Color Consistency MacAdams 2 SDCM Material Control Gear Onlor Gear Array Avray Avray Colw Auting Colw Color Temperature Color Of Housing CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K BB	Adapter Type	Array		
Control Gear on/off Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K Below BBL, 300K Below BBL, 300K Below BBL, 300K Below BBL, 300K BBL	Mounting Type	Array		
Light Distribution Array Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/830		
Wattage 50 W Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K BBL, 300K	Control Gear	on/off		
Luminous Flux 4036 Im Efficacy (Im/W) 81 Im/W COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Array		
Efficacy (Im/W) COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Wattage	50 W		
COB Flux 5550 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	4036 lm		
Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Efficacy (Im/W)	81 lm/W		
Color Rendering Index Ra 80 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	COB Flux	5550 lm		
Color Of Housing IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000 K		
IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 80		
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	White		
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Powder painted die-cast aluminium	IP Rating	20		
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)		
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,		
<u> </u>	Color Consistency	MacAdams 2 SDCM		
UGR 30.8	Material	Powder painted die-cast aluminium		
	UGR	30.8		





