Hub, version 122 RO 14 44 13 5

There are more versions of **Hub** available at <u>lival.com</u>
Architecturally simple and compact design with high cooling capacity.

	ľ	V	/ 🗡	
		•		

Article Number 122 RO 14 44 13 5 Family Name Hub Luminaire Type GA-69 Mounting Type Surface-mounted on ceiling Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) Light Source Options Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium UGR	Liebteeuwee	LED		
Family Name Luminaire Type Tracklight Adapter Type GA-69 Mounting Type Surface-mounted on ceiling Light Source Product Name Control Gear Control Gea	Lightsource	LED		
Luminaire Type GA-69 Mounting Type Surface-mounted on ceiling Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 lm Efficacy (Im/W) 88 lm/W COB Flux 4950 lm Color Temperature 3000 K Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000 K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium		122 RO 14 44 13 5		
Adapter Type GA-69 Mounting Type Surface-mounted on ceiling Light Source Product Name Citizen CLU038-1206/830 Control Gear on/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 300K BBL, 3000K BBL, 300K BBL,	Family Name	Hub		
Mounting Type Light Source Product Name Citizen CLU038-1206/830 Control Gear On/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 lm Efficacy (lm/W) 88 lm/W COB Flux 4950 lm Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing IP Rating 19 Rating 10 CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 300K Below BBL, 3000K BBL	Luminaire Type	Tracklight		
Light Source Product Name Control Gear On/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 300K BBL	Adapter Type	GA-69		
Control Gear on/off, DALI, BLL Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 300	Mounting Type	Surface-mounted on ceiling		
Light Distribution Wide Flood Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Source Product Name	Citizen CLU038-1206/830		
Wattage 42 W Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Meat 2000K, 4000K, 5000K CRI 90+ 2700K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Control Gear	on/off, DALI, BLL		
Luminous Flux 3702 Im Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Light Distribution	Wide Flood		
Efficacy (Im/W) 88 Im/W COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Meat 2000K, 4000K, 5000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Wattage	42 W		
COB Flux 4950 Im Color Temperature 3000 K Color Rendering Index Ra 80 Color Of Housing Silver IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Luminous Flux	3702 lm		
Color Temperature3000 KColor Rendering IndexRa 80Color Of HousingSilverIP Rating23Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCMMaterialPowder painted die-cast aluminium	Efficacy (Im/W)	88 lm/W		
Color Rendering IndexRa 80Color Of HousingSilverIP Rating23Lifetime50 000h (L80 B10)Light Source OptionsCRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400KColor ConsistencyMacAdams 2 SDCMMaterialPowder painted die-cast aluminium	COB Flux	4950 lm		
Color Of Housing IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Billiant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Temperature	3000 K		
IP Rating 23 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K, Filliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Rendering Index	Ra 80		
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Color Of Housing	Silver		
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	IP Rating	23		
Light Source Options 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K Color Consistency MacAdams 2 SDCM Material Powder painted die-cast aluminium	Lifetime	50 000h (L80 B10)		
Material Powder painted die-cast aluminium	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,		
<u>_</u>	Color Consistency	MacAdams 2 SDCM		
UGR 25.4	Material	Powder painted die-cast aluminium		
	UGR	25.4		





