## Lean DL, version 19K TO 27 81 13 5

There are more versions of **Lean DL** available at <u>lival.com</u> High performance recessed downlight. Tilts 90° and turns 355°, great for shelf and wall lighting.

	M	/	
ь	v	/ <u>^</u>	

Lightsource	LED		
Article Number	19K TO 27 81 13 5		
Family Name	Lean DL		
Luminaire Type	Downlight		
Adapter Type	Array		
Mounting Type	Array		
Light Source Product Name	Citizen CLU048-1212/930BBL		
Control Gear	on/off, BLL		
Light Distribution	Array		
Wattage	55 W		
Luminous Flux	5027 lm		
Efficacy (Im/W)	91 lm/W		
COB Flux	5750 lm		
Color Temperature	3000 K		
Color Rendering Index	Ra 90		
Color Of Housing	Silver		
IP Rating	23		
Lifetime	50 000h (L80 B10)		
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K		
Color Consistency	MacAdams 2 SDCM		
Material	Powder painted die-cast aluminium		
UGR	22.2		





