

# Lean Mini, version 19L O0 14 44 13 6

There are more versions of **Lean Mini** available at [lival.com](http://lival.com)  
Compact Lean variation. Flush installation on lighting track, perfect for recessed tracks.



|                           |                                                                                                                                                                  |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lightsource               | LED                                                                                                                                                              |
| Article Number            | 19L O0 14 44 13 6                                                                                                                                                |
| Family Name               | Lean Mini                                                                                                                                                        |
| Luminaire Type            | Tracklight                                                                                                                                                       |
| Adapter Type              | Array                                                                                                                                                            |
| Mounting Type             | Array                                                                                                                                                            |
| Light Source Product Name | Citizen CLU038-1206/830                                                                                                                                          |
| Control Gear              | on/off, BLL                                                                                                                                                      |
| Light Distribution        | Array                                                                                                                                                            |
| Wattage                   | 36 W                                                                                                                                                             |
| Luminous Flux             | 3744 lm                                                                                                                                                          |
| Efficacy (lm/W)           | 104 lm/W                                                                                                                                                         |
| COB Flux                  | 4350 lm                                                                                                                                                          |
| Color Temperature         | 3000 K                                                                                                                                                           |
| Color Rendering Index     | Ra 80                                                                                                                                                            |
| Color Of Housing          | White                                                                                                                                                            |
| IP Rating                 | 20                                                                                                                                                               |
| Lifetime                  | 50 000h (L80 B10)                                                                                                                                                |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM                                                                                                                                                  |
| Material                  | Powder painted die-cast aluminium                                                                                                                                |
| UGR                       | 24.6                                                                                                                                                             |

