Meteor, version 150 R0 19 81 11 6

There are more versions of **Meteor** available at <u>lival.com</u>
Deep downlight with low glare and excellent light output. 1m cable included, other options available by request.

	W	7/578	
		/ <u>^</u>	

Article Number 150 R0 19 81 11 6 Family Name Meteor Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 Im Efficacy (Im/W) 73 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Meat 2000K, 8000K, 8000K	Lightsource	LED	
Luminaire Type Downlight Adapter Type Array Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 Im Efficacy (Im/W) 73 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 5000K Meat	Article Number	150 RO 19 81 11 6	
Adapter Type Array Mounting Type Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 Im Efficacy (Im/W) 73 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3500K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat	Family Name	Meteor	
Mounting Type Array Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 Im Efficacy (Im/W) 73 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 5000K Meat 2000K, 5000K Meat 2000K, 5000K Meat 2000K, 5000K Meat 2000K	Luminaire Type	Downlight	
Light Source Product Name Citizen CLU038-1206/930BBL Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 lm Efficacy (lm/W) COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K	Adapter Type	Array	
Control Gear on/off, DALI, BLL Light Distribution Array Wattage 41 W Luminous Flux 3001 lm Efficacy (lm/W) 73 lm/W COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K Pelow BBL, 3500K Below BBL, 3000K BBL,	Mounting Type	Array	
Light Distribution Array Wattage 41 W Luminous Flux 3001 lm Efficacy (lm/W) 73 lm/W COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K Pelow BBL, 3000K Below BBL, 3000K	Light Source Product Name	Citizen CLU038-1206/930BBL	
Wattage 41 W Luminous Flux 3001 lm Efficacy (Im/W) 73 lm/W COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BB	Control Gear	on/off, DALI, BLL	
Luminous Flux 3001 lm Efficacy (Im/W) 73 lm/W COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K Below BBL, 3500K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 4000K	Light Distribution	Array	
Efficacy (Im/W) 73 Im/W COB Flux 4050 Im Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3000K, 4000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K,	Wattage	41 W	
COB Flux 4050 lm Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3500K Below BBL, 3000K BB	Luminous Flux	3001 lm	
Color Temperature 3000K Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K BBL, 3000K Below BBL, 3000K Below BBL, 3000K BBL, 30	Efficacy (Im/W)	73 lm/W	
Color Rendering Index Ra 90 Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K, 5000K Meat 2000K Meat	COB Flux	4050 lm	
Color Of Housing White IP Rating 20 Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, 4000K, 5000K Meat 2000K,	Color Temperature	3000K	
IP Rating	Color Rendering Index	Ra 90	
Lifetime 50 000h (L80 B10) CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, 5000K Meat 2000K,	Color Of Housing	White	
CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,	IP Rating	20	
5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K,	Lifetime	50 000h (L80 B10)	
Daket y 2400K	Light Source Options	5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K,	
Color Consistency MacAdams 2 SDCM	Color Consistency	MacAdams 2 SDCM	
Material Powder painted die-cast aluminium	Material	Powder painted die-cast aluminium	
UGR 18.1	UGR	18.1	





