



Meteor, version 150 T0 27 81 12 5

There are more versions of **Meteor** available at lival.com
Deep downlight with low glare and excellent light output. 1m cable included, other options available by request.



Lightsource	LED
Article Number	150 T0 27 81 12 5
Family Name	Meteor
Luminaire Type	Downlight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU048-1212/930BBL
Control Gear	on/off, DALI, BLL
Light Distribution	Array
Wattage	53 W
Luminous Flux	4336 lm
Efficacy (lm/W)	82 lm/W
COB Flux	5750 lm
Color Temperature	3000K
Color Rendering Index	Ra 90
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	19.5



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511