

Mini Lean DL, version 19M O0 14 81 14 5

There are more versions of **Mini Lean DL** available at lival.com
 Compact and efficient recessed downlight. Tilts 90° and turns 355°,
 designed for accent lighting.



Lightsource	LED
Article Number	19M O0 14 81 14 5
Family Name	Mini Lean DL
Luminaire Type	Downlight
Adapter Type	Cable, 1 m
Mounting Type	Recessed in ceiling
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	Standard
Light Distribution	Narrow Flood
Wattage	36 W
Luminous Flux	3464 lm
Efficacy (lm/W)	96 lm/W
COB Flux	4350 lm
Color Temperature	3000 K
Color Rendering Index	Ra 80
Color Of Housing	Silver
IP Rating	23
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	21.8

