

Nano 1200, version 15V D0 48 F8 98 5

There are more versions of **Nano 1200** available at lival.com
Linear luminaire with excellent energy efficiency and lumen output.
Quick GA-69 adapters. Opal diffuser creates soft light for general lighting.



| | |
|---------------------------|--|
| Lightsource | LED |
| Article Number | 15V D0 48 F8 98 5 |
| Family Name | Nano 1200 |
| Luminaire Type | Linear |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | TCI LED Nano1200 840/4000K |
| Control Gear | on/off, DALI |
| Light Distribution | Array |
| Wattage | 81 W |
| Luminous Flux | 10383 lm |
| Efficacy (lm/W) | 128 lm/W |
| COB Flux | 12100 lm |
| Color Temperature | 4000K |
| Color Rendering Index | Ra 80 |
| Color Of Housing | Silver |
| IP Rating | 23 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 29.3 |

