


# Nano 2400, version 168 D2 48 F8 A3 9

There are more versions of **Nano 2400** available at [lival.com](http://lival.com)  
Linear luminaire with excellent energy efficiency and lumen output.  
Quick GA-69 adapters. Microprismatic diffuser reduces glare.



|                           |                                                                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Lightsource               | LED                                                                                                                                                                             |
| Article Number            | 168 D2 48 F8 A3 9                                                                                                                                                               |
| Family Name               | Nano 2400                                                                                                                                                                       |
| Luminaire Type            | Linear                                                                                                                                                                          |
| Adapter Type              | Array                                                                                                                                                                           |
| Mounting Type             | Array                                                                                                                                                                           |
| Light Source Product Name | TCI LED Nano1200 840/4000K                                                                                                                                                      |
| Control Gear              | on/off, DALI                                                                                                                                                                    |
| Light Distribution        | Array                                                                                                                                                                           |
| Wattage                   | 158 W                                                                                                                                                                           |
| Luminous Flux             | 20319 lm                                                                                                                                                                        |
| Efficacy (lm/W)           | 129 lm/W                                                                                                                                                                        |
| COB Flux                  | 12100 lm                                                                                                                                                                        |
| Color Temperature         | 4000K                                                                                                                                                                           |
| Color Rendering Index     | Ra 80                                                                                                                                                                           |
| Color Of Housing          | Black                                                                                                                                                                           |
| IP Rating                 | 23                                                                                                                                                                              |
| Lifetime                  | 50 000h (L80 B10)                                                                                                                                                               |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K,<br>5000K CRI 90+ 2700K Below BBL,<br>3000K Below BBL, 3500K Below<br>BBL, 4000K Brilliant vivid 3000K,<br>4000K, 5000K Meat 2000K,<br>Bakery 2400K |
| Color Consistency         | MacAdams 2 SDCM                                                                                                                                                                 |
| Material                  | Powder painted die-cast aluminium                                                                                                                                               |
| UGR                       | 26.3                                                                                                                                                                            |



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511