




Nano 800, version 129 D0 44 44 A3 9

There are more versions of **Nano 800** available at lival.com
Linear luminaire with excellent energy efficiency and lumen output.
Quick GA-69 adapters. Microprismatic diffuser reduces glare.



Lightsource	LED
Article Number	129 D0 44 44 A3 9
Family Name	Nano 800
Luminaire Type	Linear
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	TCI LED Nano800 840/4000K
Control Gear	on/off, DALI
Light Distribution	Array
Wattage	54 W
Luminous Flux	7043 lm
Efficacy (lm/W)	130 lm/W
COB Flux	8000 lm
Color Temperature	4000K
Color Rendering Index	Ra 80
Color Of Housing	Black
IP Rating	23
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	26.5



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511