




# Nano 800, version 129 D0 43 44 A3 5

There are more versions of **Nano 800** available at [lival.com](http://lival.com)  
Linear luminaire with excellent energy efficiency and lumen output.  
Quick GA-69 adapters. Microprismatic diffuser reduces glare.



Lightsource	LED
Article Number	129 D0 43 44 A3 5
Family Name	Nano 800
Luminaire Type	Linear
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	TCI LED Nano800 830/3000K
Control Gear	on/off, DALI
Light Distribution	Array
Wattage	54 W
Luminous Flux	6643 lm
Efficacy (lm/W)	123 lm/W
COB Flux	7800 lm
Color Temperature	3000K
Color Rendering Index	Ra 80
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	
Material	Powder painted die-cast aluminium
UGR	26.2



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511