



# Nano-X 2400, version 11L D2 48 F8 MP 5

There are more versions of **Nano-X 2400** available at [lival.com](http://lival.com)  
High lumen output and excellent glare control makes Nano-X a perfect fit for retail and office use. Fitted with microprismatic lens for glare reduction.



|                           |  |
|---------------------------|--|
| Lightsource               | LED  |
| Article Number            | 11L D2 48 F8 MP 5  |
| Family Name               | Nano-X 2400  |
| Luminaire Type            | Linear   |
| Adapter Type              | Array  |
| Mounting Type             | Array  |
| Light Source Product Name | TCI LED Nano1200 840/4000K   |
| Control Gear              | on/off, DALI   |
| Light Distribution        | Array  |
| Wattage                   | 160 W  |
| Luminous Flux             | 12822 lm   |
| Efficacy (lm/W)           | 80 lm/W  |
| COB Flux                  | 12100 lm   |
| Color Temperature         | 4000K  |
| Color Rendering Index     | Ra 80  |
| Color Of Housing          | Silver   |
| IP Rating                 | 20   |
| Lifetime                  | 50 000h (L80 B10)  |
| Light Source Options      | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency         | MacAdams 3 SDCM  |
| Material                  | Powder painted die-cast aluminium  |
| UGR                       | 18.7   |



For more information and DLX & LDT downloads visit us at [lival.com](http://lival.com). We are more than happy to reply to your email at [lival@lival.com](mailto:lival@lival.com) or your call at +358-9-235 511