



QS Standard, version 187 N0 19 81 12 9

There are more versions of **QS Standard** available at lival.com
Designed to be an architectural element, Quick Step creates a recess in the ceiling. Simple and cost-effective Standard head.



Lightsource	LED
Article Number	187 N0 19 81 12 9
Family Name	QS Standard
Luminaire Type	Downlight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/930BBL
Control Gear	on/off, DALI
Light Distribution	Array
Wattage	34 W
Luminous Flux	2915 lm
Efficacy (lm/W)	86 lm/W
COB Flux	3360 lm
Color Temperature	3000K
Color Rendering Index	Ra 90
Color Of Housing	Black
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	20.5



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511