# QS Standard, version 187 N0 19 81 13 6

There are more versions of **QS Standard** available at lival.com
Designed to be an architectural element, Quick Step creates a recess in the ceiling. Simple and cost-effective Standard head.

| | |
|---|---|
| Lightsource | LED |
| Article Number | 187 N0 19 81 13 6 |
| Family Name | QS Standard |
| Luminaire Type | Downlight |
| Adapter Type | Array |
| Mounting Type | Array |
| Light Source Product Name | Citizen CLU038-1206/930BBL |
| Control Gear | on/off, DALI |
| Light Distribution | Array |
| Wattage | 34 W |
| Luminous Flux | 2789 lm |
| Efficacy (lm/W) | 82 lm/W |
| COB Flux | 3360 lm |
| Color Temperature | 3000K |
| Color Rendering Index | Ra 90 |
| Color Of Housing | White |
| IP Rating | 20 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 25 |






