

Secur 812, version 12A 00 19 12 12 9

There are more versions of **Secur 812** available at <u>lival.com</u> Versatile pendant luminaire, a great fit to all applications from cafeterias to food displays. Supplied with a 3 m cable, other lengths by request.

Lightsource	LED
Article Number	12A OO 19 12 12 9
Family Name	Secur 812
Luminaire Type	Pendant
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/930BBL
Light Source Product Name	Citizen CLU038-1206/930BBL on/off, DALI, BLL
Control Gear	on/off, DALI, BLL
Control Gear Light Distribution	on/off, DALI, BLL Array
Control Gear Light Distribution Wattage	on/off, DALI, BLL Array 36 W
Control Gear Light Distribution Wattage Luminous Flux	on/off, DALI, BLL Array 36 W 3064 Im
Control Gear Light Distribution Wattage Luminous Flux Efficacy (Im/W)	on/off, DALI, BLL Array 36 W 3064 Im 85 Im/W
Control Gear Light Distribution Wattage Luminous Flux Efficacy (Im/W) COB Flux	on/off, DALI, BLL Array 36 W 3064 Im 85 Im/W 3530 Im
Control Gear Light Distribution Wattage Luminous Flux Efficacy (Im/W) COB Flux Color Temperature	on/off, DALI, BLL Array 36 W 3064 Im 85 Im/W 3530 Im 3000 K







Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	21