## Secur 816, version 12C RO 19 12 11 6

There are more versions of **Secur 816** available at <u>lival.com</u>
Versatile pendant luminaire, a great fit to all applications from cafeterias to food displays. Supplied with a 3 m cable, other lengths by request.

	V	<u> </u>	

Lightsource	LED		
Article Number	12C RO 19 12 11 6		
Family Name	Secur 816		
Luminaire Type	Pendant		
Adapter Type	Array		
Mounting Type	Array		
Light Source Product Name	Citizen CLU038-1206/930BBL		
Control Gear	on/off, DALI, BLL		
Light Distribution	Array		
Wattage	43 W		
Luminous Flux	3470 lm		
Efficacy (Im/W)	81 lm/W		
COB Flux	4050 lm		
Color Temperature	3000 K		
Color Rendering Index	Ra 90		
Color Of Housing	White		
IP Rating	23		
Lifetime	50 000h (L80 B10)		
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K		
Color Consistency	MacAdams 2 SDCM		
Material	Powder painted die-cast aluminium		
UGR	17.8		





