



Secur 816, version 12C R0 19 12 12 6

There are more versions of **Secur 816** available at lival.com
Versatile pendant luminaire, a great fit to all applications from cafeterias to food displays. Supplied with a 3 m cable, other lengths by request.



Lightsource	LED
Article Number	12C R0 19 12 12 6
Family Name	Secur 816
Luminaire Type	Pendant
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/930BBL
Control Gear	on/off, DALI, BLL
Light Distribution	Array
Wattage	43 W
Luminous Flux	3311 lm
Efficacy (lm/W)	77 lm/W
COB Flux	4050 lm
Color Temperature	3000 K
Color Rendering Index	Ra 90
Color Of Housing	White
IP Rating	23
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	21.5



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511