

Trigger Mini Standard, version 164 00 19 44 12 9



There are more versions of **Trigger Mini Standard** available at

lival.com

Classic Standard head in a flush installed housing. High lumen output in a cost efficient luminaire.



Lightsource	LED
Article Number	164 00 19 44 12 9
Family Name	Trigger Mini Standard
Luminaire Type	Tracklight
Adapter Type	Array
Mounting Type	Array
Light Source Product Name	Citizen CLU038-1206/930BBL
Control Gear	on/off, DALI
Light Distribution	Array
Wattage	35 W
Luminous Flux	3140 lm
Efficacy (lm/W)	90 lm/W
COB Flux	3530 lm
Color Temperature	3000K
Color Rendering Index	Ra 90
Color Of Housing	Black
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	20.7



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your email at lival@lival.com or your call at +358-9-235 511